

Wet vacuum WSP 2000



This vacuum has endless possibilities

- Vacuum in multi-locations and transport the liquid to a discharge area
- Vacuum large areas and volumes of liquids pumping automatically to a discharge area.



The vacuum cleaner is easy to empty by opening the ball valve and letting the liquid drain out.



Lid for emptying out residual and coarse dirt is unlocked by operating the foot pedal, lid pulled towards rear.



Inside view with installed pump and float switch for suction engine and pump.



The pump is easy to remove, residual dirt emptying lid opened for easy overall cleaning

- Pneumatic rear wheels provide stability on rough surfaces.
- The vacuum producer is available in 1,2 kW.
- More motorrating optional available.
- The vacuum is automatically turned off when a predetermined liquid level is reached within the housing.
- Easy cleaning because the pump is easy to remove.

Housing	GRP
Motorrating (kW)	1,2
Voltage (Volt)	230
Frequency (Hz)	50
Vacuum (mbar)	230
Volume flow (m ³ /h)	174
Inlet (mm)	50 Ø
Weight (kg) (without/with pump)	44/54
Protection class	IP x4
Liquid capacity (ltr.)	45 to 100
Length x Width x Height (mm)	850 x 700 x 950
Optional available with pump	
Fluid quantity (m ³ /h) (1m delivery height)	18
Max. delivery height (m)	9

Ruwac
Industrial vacuums



RUWAC ASIA - Expert Consultancy - Testing - Service - Spare parts

Project Partners CO.Ltd.
Dr. Gerhard Link Bldg. 14th Floor
88, Krungthepkreetha Rd.
10240 Bangkok - Thailand

Tel.: +66 2 379 4277
Fax: +66 2 379 4278
sales@ruwac-asia.com
www.ruwac-asia.com

Dealer/After-Sales Service: