

TECHNICAL DATA

Product Group : Mobile Vacuum - Electrical Drive

Product Name : DS 1150 ALK



Model	DS 1150 ALK	DS 1150 ALK	DS 1150 ALK
Drive Type	Single Phase AC + Starting Capacitor	Single Phase AC + Starting Capacitor	Single Phase AC + Starting Capacitor
Power in Kw	1.5	1.5	1.5
Sound as per DIN db (A)	64	64	64
Weight in Kg	80	80	80
Dimensions in mm			
Width	520	520	520
Length	850	850	850
Height	890	970	1210
Allowed Operation Time	Continuous Operation	Continuous Operation	Continuous Operation
Dust Bin Size in L	35	35	35
Effective Collection Capacity in L	28	28	28
ATEX Zone	Atex Zone 22 II 3 D	Atex Zone 22 II 3 D	Atex Zone 22 II 3 D
Manometer	Included	Included	Included
Main filter			
Filter Type	Cell	Pocket	Pocket
Filter Size m ²	1	1.2	2.6
Filter Class	L	M	M
Performance			
Vacuum mBar	180	180	180
Air volume m ³ /h	250	250	250
Suitable for Explosive Suction Media	No	Yes and subject to ATEX Zone and suction media properties. Customization and options available.	
Model Feature	GRP antistatic modular housing. No friction and impact sparks. Corrosion resistant and non rusting.		

Customizing , Options and Accessories

To find all available additional features , options and accessories visit:

www.ruwac-asia.com