



TECHNICAL DATA

Product Group : Mobile Vacuum - Electrical Drive

Product Name : DS 1220

Model	DS 1220	DS 1220	DS 1220	DS 1220
Drive Type	3 Phase Current	3 Phase Current	3 Phase Current	3 Phase Current
Power in Kw	2.2	2.2	2.2	2.2
Sound as per DIN db (A)	70	70	70	70
Weight in Kg	85	85	85	85
Dimensions in mm				
Width	520	520	520	520
Length	850	850	850	850
Height	1223	970	1223	1223
Allowed Operation Time	Continuous Operation	Continuous Operation	Continuous Operation	Continuous Operation
Dust Bin Size in L	35	35	35	35
Effective Collection Capacity in L	28	28	28	28
ATEX Zone	Atex Zone 22 II 3 D	Atex Zone 22 II 3 D	Atex Zone 22 II 3 D	Atex Zone 22 II 3 D
Manometer	Included	Included	Included	Included
Main filter				
Filter Type	Cell	Pocket	Pocket	Pocket
Filter Size m ²	1	1.2	2.6	2.6
Filter Class	L	M	M	M
Performance				
Vacuum mBar	206	206	206	206
Air volume m ³ /h	270	270	270	250
Suitable for Explosive Suction Media	No	Yes and subject to ATEX Zone and suction media properties. Customization and options available.		
Model Feature	GRP antistatic modular housing. No friction and impact sparks. Corrosion resistant and non rusting.			

Customizing , Options and Accessories

To find all available additional features , options and accessories visit:

www.ruwac-asia.com