



TECHNICAL DATA

Product Group : Mobile Vacuum - Electrical Drive

Product Name : DS 1220 ALK

Model	DS 1220 ALK	DS 1220 ALK	DS 1220 ALK
Drive Type	Single Phase AC + Starting Capacitor	Single Phase AC + Starting Capacitor	Single Phase AC + Starting Capacitor
Power in Kw	2.2	2.2	2.2
Sound as per DIN db (A)	70	70	70
Weight in Kg	85	85	85
Dimensions in mm			
Width	520	520	520
Length	850	850	850
Height	970	970	1223
Allowed Operation Time	Continuous Operation	Continuous Operation	Continuous Operation
Dust Bin Size in L	35	35	35
Effective Collection Capacity in L	28	28	28
ATEX Zone	Atex Zone 22 II 3 D	Atex Zone 22 II 3 D	Atex Zone 22 II 3 D
Manometer	Included	Included	Included
Main filter			
Filter Type	Cell	Pocket	Pocket
Filter Size m ²	1	1.2	2.6
Filter Class	L	M	M
Performance			
Vacuum mBar	270	270	270
Air volume m ³ /h	206	206	206
Suitable for Explosive Suction Media	No	Yes and subject to ATEX Zone and suction media properties. Customization and options available.	
Model Feature	GRP antistatic modular housing. No friction and impact sparks. Corrosion resistant and non rusting.		

Customizing , Options and Accessories

To find all available additional features , options and accessories visit:

www.ruwac-asia.com