

Inductive motor vacuums

DS 2410

DS 2420

DS 2520

DS 2720



High capacity vacuums



Foot lever actuated dust pan

- Extremely strong, corrosion-proof GRP body
- Modular system, can be upgraded at any time
- Compact dimensions:
length 920 mm x width 730 mm
- Complete system, including sound proofing
- Suitable for round-the-clock operation
- Minimum filter surface load
- Simple filter change

	DS 2410	DS 2420	DS 2520	DS 2720
Motor (kW) / (H.P.)	4,0	4,0	5,5	7,5
Voltage (Volt)	400	400	400	400
Vacuum (mbar)	190	170	230	210
*1) Volume (m ³ /h)	410	540	650 / (770*2)	690 / (820*2)
Filter area (m ²) / (ft ²)	2,4 / 4,5	2,4 / 4,5	2,4 / 4,5	2,4 / 4,5
Height (mm) (with residualfilter +160 mm)	1.220 / 1.590	1.220 / 1.590	1.250 / 1.620	1.250 / 1.620
Weight (kg)	94	102	127	133
Noise factor (dB(A))	72	74	75	77

*1) Air volume measured with 3 meter hose and coated filter, TÜV certified.

*2) Hose, Ø 100 mm diameter.



DIN EN 60335-2-69, Anh. CC



ATEX 94/9/EG



RUWAC
Industriesauger GmbH

Westhoyeler Str. 25
49328 Melle-Riemsloh

Telefon: 0 52 26 - 98 30-0
Telefax: 0 52 26 - 98 30-44

Web: www.ruwac.de
E-Mail: ruwac@ruwac.de

